

4POE Output+1POE input 100m

Distance POE Extender



- ✧ 1 * IEEE802.3af/at/bt (PoE/90w) input
- ✧ 1 * IEEE802.3af/at/bt (PoE/60w) output
- ✧ 3 * IEEE802.3af/at (PoE) output
- ✧ Vlan,

Application:

- ✧ Wireless Access Point
- ✧ IP Camera
- ✧ IP Phone
- ✧ Computer Networks

POE Port	IEEE 802.3af/at/bt
Output Power	1-3 port max 30W, 4 port max 60W
Power input Pin	1/2+, 3/6-, 4/5+, 7/8-
Power output pin	1-3 port (1/2+, 3/6-) 4 port (1/2+, 3/6-, 4/5+, 7/8-)
Whole Power	≤90W
POE Protocol	IEEE 802.3af/at/bt
Power Distance	≤100m
Network Standard	IEEE802.3, IEEE802.3u, IEEE802.3x
Network Medium	10/100、1000BASE-TX:5 class and above non shielded twisted pair
Data Distance	≤100m
Switch Capability	10Gbps
Forwarding Rate	10BASE-tx:14880pps/port 100BASE-tx: 14800pps/port 1000BASE-tx: 148000pps/port
MAC Address	MAC address table 1K
Port Function	Power priority mechanism, fast and forward, MAC automatic learning and aging IEEE802.3X Full-duplex and mode and backpressure for Half-duplex mode
Working Environment	Working temperature: -10° -- 55° C
Weight	160g ± 5%
Size	(Length) 98mm*(Width) 148mm*(High) 34mm

Product	10/100/1000Mbps POE Extender
Model	EX-SW1004G-OUT