


Photo		
Feature	<ul style="list-style-type: none"> <li>• 20W foldable solar panel, integrated installation or split installation</li> <li>• 24 hours long recording + low power sleep dual mode</li> <li>• Built-in large-capacity lithium battery, supporting 7 days * 24 hours of video recording in rainy days</li> <li>• Using high-performance ISP and 1/2.7" black light image sensor</li> <li>• 1920*1080P hd video</li> <li>• Built-in microphone and speaker, support two-way voice intercom</li> <li>• Support cloud storage + local storage.</li> <li>• APP Support Android/Apple IOS</li> <li>• Metal shell, IP65 outdoor waterproof</li> <li>• The package of the whole machine is light in weight and small in size</li> </ul>	
Model	EX-USL100RB-4G724	
	<b>clarity</b>	<b>2MP</b>
comprehensive	Master chip	Ingenic-T31ZL
	Image Sensor	GC2063
	APP operating system	Android, IOS
	Image Sensor	1/2.7" Image Sensor
	Compression format	H.264+/H.265
Networking	4G	TD-LTE,TD-LTE / LTE FDD TD-LTE / LTE-FDD

Networking method	4G module version	Chinese version/US version/European version/Southeast Asian version/Japanese version/Australian version (optional)
alarm mode	detection mode	PIR human body induction + AI humanoid detection
	Detection distance	0-12M
	detection angle	95°
	Alarm method	Call mobile phone or push information in real time
PTZ	PTZ Angel	Horizontal 355° Vertical 100°
	Rotating speed	Horizontal 55°/sec Vertical 40°/sec
NIGHT VISION MODE	Full color night vision	Illumination 0.00LUX
	Infrared light	Infrared LED distance 30M
	White light	White LED distance 30M
VOICE	built-in speaker	3W
	built-in microphone	Monitoring range 20M
Lens	focal length	3.6mm
	Angle	95°
Storage	Cloud Storage	Cloud storage (alarm event recording)
	Local Storage	TF card (Maximum 128G can record for 20-25 days)
Power	power supply mode	Solar panel + battery
	Solar cell material	Monocrystalline silicon
	Solar battery power	20W
	Battery	8pcs 18650 battery 24000MAH
	Maximum working power	4W
	Standby power	0.003W
	working environment	indoor/outdoor

Other	Operating temperature	-30°~+60°
	Working humidity	0%~90%RH
Packing	net weight	3.8kg/pcs
	Color box size	340*240*180mm
	Packing Quantity	4pcs
	FCL weight	16.5KG/CTN
	Carton size	355*494*380mm